

B200 XP

HYDRAULIC PILING RIG
ATTREZZATURA IDRAULICA PER PALI



Designed to work on the most difficult sites and has excellent technical characteristics: 240 kN high speed winch for fast work, the H22 rotary head has a maximum torque output of 210 kNm and speed up to 34 rpm, it is ideal for drilling large and small diameter boreholes and for driving long casings.

"Keep the operator happy in a comfortable working environment" is our formula for added productivity. The B200 XP is designed to satisfy the European Union standards on safety and is manufactured to comply with the ISO 9001 requirements on quality.





B200 XP

PERFORMANCE

PRESTAZIONI

BORED PILES		PALI
Max. depth		Profondità max. 68 m
Max. diameter under mast		Diametro max. sotto mast 3200 mm
Max. diameter - Labyrinth / Screw joint - Crowd ram		Diametro max. - Giunto labirinto/vite - Martinetto pull down 1800/1500 mm
Max. diameter - Labyrinth / Screw joint - Crowd winch		Diametro max. - Giunto labirinto/vite - Argano pull down 1500/1300 mm
Max. diameter with casing oscillator		Diametro max. morsa giracolonna 1500 mm
C.F.A. PILES		PALI C.F.A.
Max. depth		Profondità max. 26,8 m
Max. diameter		Diametro max. 1000 mm
DISPLACEMENT PILES		DISPLACEMENT PILES
Max. depth		Profondità max. 25 m
Max. diameter		Diametro max. 520 mm
SOIL MIXING		SOIL MIXING
Max. depth		Profondità max. 25,4 m
Max. diameter		Diametro max. 1000 mm
DIAPHRAGM WALL		DIAFRAMMI
Max. depth with KRC		Profondità max. con KRC 37,5 m



“Somos tu mejor solución...
Sin importar el tamaño de tus proyectos”

Oficina Central

Presidencia Salinillas 306-1, Irrigación 11500, CDMX. Tel. (52-55) 5395 - 0305

Patio y Sucursal Querétaro

Carr. Querétaro-San Luis Potosí km 17+ 340, El Salitre Querétaro. Tel. (52-442) 628-2093

Oficinas Regionales: Monterrey / Torreón / Guadalajara